



SPECIFICATIONS All specifications at ambient of 25 °C, unless specified otherwise

<p>INPUTS</p> <p>No. of inputs 1</p> <p>Input group 1</p> <p> Thermocouple B, E, J, K, N, R, S, T</p> <p> RTD Pt100, 3-wire</p> <p> Voltage 0~50 mV (Lin2)</p> <p> Current 20~4mA, 0~20mA, 4~20mA</p> <p>Input group 2</p> <p> Thermocouple B, C, D, E, G, J, K, N, R, S, T</p> <p> RTD Pt100, 3-wire, Cu53</p> <p> Current 0~20 mA, 4~20 mA, Square root (for input 1)</p> <p> Voltage 0~50 mV</p> <p> Through DIP selection following voltage inputs are available : 0~1 V, 0~5 V, 0~10 V, 0~10 mV, 0~100 mV, 0~200 mV</p> <p>Transmitter supply 22 V nominal, 30 mA max</p> <p>Range limits See Table 1</p> <p>Accuracy See Table 1</p> <p>Cold junction compensation Automatic</p> <p>Sensor break protection User programmable</p> <p>INDICATION</p> <p>Process variable Upper display : 4 digit, 7 segment 2" (50.8 mm) red LED display</p> <p>Lower display : 4 digit, 7 segment 0.56" (14.2 mm) red LED display</p> <p>Unit</p>	<p>PROGRAMMABLE PARAMETERS</p> <p>Unit None, °C, °F, °K, EU, bar, PSI, PH°BAR, °PSI, °pH, °Pa, %RH, rpm, %, ^E, V, mV, A, mA, W, m, cm, g, kg, mmHg, LPM, LPH, cal</p> <p>Resolution User selectable</p> <p>0.01, 0.1 or 1 for linear input, 0.1 or 1 for temperature</p> <p>High scale Full range (See Table 1)</p> <p>Low scale Full range (See Table 1)</p> <p>Digital filter A (minimum) ~ F (maximum)</p> <p>Level lock ON, OFF</p> <p>OTHER</p> <p>Keypad Tactile, membrane</p> <p>Programming Through 3 keys</p> <p>Dimensions (in mm) 200(H) x 300(W) x 130(D)</p> <p>Enclosure material MS sheet, 20 SWG</p> <p>Finish Powder coated, Siemens Grey, RAL-7032</p> <p>Weight 5 kg</p> <p>Mounting Wall mount</p> <p>Connections Heavy duty round-shell connectors</p> <p>Supply voltage 230 V AC 10%, 50/60 Hz</p> <p>Power consumption 24 watts maximum</p> <p>Operating ambient temperature 0~50 °C</p> <p>Relative humidity Below 90%, non condensing</p>
--	---

PROGRAMMABLE TEMPERATURE INDICATOR ————— XALD2

2" CHARACTER HEIGHT, UNIVERSAL INPUT

TABLE 1


SENSOR / INPUT	RANGE LIMITS (°C / EU)		RANGE IN WHICH ACCURACY IS SPECIFIED		TYPICAL ACCURACY AT 30 °C (°C / EU)	WORST CASE ACCURACY (°C / EU)
	LOW SCALE	HIGH SCALE	LOW SCALE	HIGH SCALE		
Input Group 1						
Pt - 6% Rh / Pt - 30% Rh (B)	400	1820	400	1820	± 3	± 5
Chromel / Constantan (E)	-270	1000	0	1000	± 1	± 3
Iron / Constantan (J)	-210	760	0	760	± 1	± 3
Chromel / Alumel (K)	-270	1372	-50	1200	± 1	± 3
Nicrosil / Nisil (N)	-270	1300	-50	1200	± 1	± 3
Pt / Pt - 13% Rh (R)	0	1760	400	1760	± 2	± 5
Pt / Pt - 10% Rh (S)	0	1760	400	1760	± 2	± 5
Copper / Constantan (T)	-270	400	-200	400	± 1	± 3
Pt100, 3-wire	-200	850	-200	600	± 0.3	± 1.0
Linear (0~50 mV, 0~20 mA, 4~20 mA)	-1999	9999	-1999	9999	± 5 EU	± 20 EU

Input Group 2


The following inputs are available in Input Group 2 in addition to inputs of Input Group 1.

Tungsten - 5% Rh / Tungsten - 26% Rh (C)	0	2320	0	2320	± 3	± 5
Tungsten - 3% Rh / Tungsten - 25% Rh (D)	0	2310	0	2310	± 3	± 5
Tungsten / Tungsten - 26% Rh (G)	0	2310	0	2310	± 3	± 5
Cu53	0	180	0	180	± 0.3	± 0.5
Linear (0~10 mV, 0~100 mV, 0~200 mV, 0~1 V, 0~5 V, 0~10 V)	-1999	9999	-1999	9999	± 5 EU	± 20 EU
Linear (4~20 mA) with square root	0	9999	0	9999	± 10 EU	± 40 EU

CONNECTION DIAGRAM



ORDERING INFORMATION



AN ISO 9001:2000 COMPANY

SALES INQUIRIES

1800-22-radix
1800-22-7234

www.radix.co.in

Radix Electrosystems Pvt Ltd
B-14, 2nd Floor, Ghanshyam Indl Estate
Veera Desai Road, Andheri (W)
Mumbai - 400 053, India
Tel : + 91 22 26730101 Fax : + 91 22 26731891
Email : sales@radix.co.in www.radix.co.in
Exports email : exports@radix.co.in

BANGALORE C : 0-9341063830
BARODA C : 0-9376215882
CHANDIGARH C : 0-9313560869
CHENNAI C : 0-9381056345
CHHATISGARH C : 0-9337002344
COIMBATORE C : 0-9380284497
GOA C : 0-9371439090

GWALIOR C : 0-9322245543
HP C : 0-9313560869
HYDERABAD C : 0-9391053480
INDORE C : 0-9301995060
KARNATAKA C : 0-9341063831
KERALA C : 0-9341273814
NAGPUR C : 0-9322245543

NEW DELHI C : 0-9312600076
T : 011-25786350
ORISSA C : 0-9337002344
PUNE C : 0-9371113404
T : 020 24479759
PUNJAB C : 0-9312600076