




Series
DL7

Differential Pressure Data Logger

Also Measures and Logs Temperature, Self-Powered, 2-Channel, Compact



Monitor and Record low differential pressures and temperature with the Model DL7 Differential Pressure Data Logger. Unit includes an on-board thermistor for ambient temperature measurement. Sampling rates are user selectable from 0.04 s to 8 hrs with First-in first-out or Fill-then-stop sampling options. Loggers can store up to 21,500 readings and operate totally independently from any external power supply with built-in lithium battery. Use Model DL200 Windows® software (sold separately) to quickly program the logger or upload data to a computer. The Series DL7 logger is ideal for monitoring air duct velocity, testing and balancing HVAC systems, or verifying room pressure.

Model	Pressure Range
DL70	±0.5 in w.c. (1.2 mbar)
DL71	±1 in w.c. (2.5 mbar)
DL72	±2.0 in w.c. (5.0 mbar)
DL75	±5 in w.c. (12.4 mbar)
DL710	±10 in w.c. (24.9 mbar)

ACCESSORY

DL200, Windows® Software and Connecting Cable

SPECIFICATIONS

No. of Channels: Two; internal thermistor, and a differential pressure sensor.
Internal Thermistor Range: -40 to 158°F (-40 to 70°C).
Compensated Temp Range: 32 to 158°F (0 to 70°C).
Memory Size: 21,500 readings.
Accuracy: ±0.05 w.c. (up to 2" range) ±0.1 (5" and 10" range).
Thermal Accuracy: ±0.5% FS.
Clock Accuracy: ±2 s/day plus one sampling interval.
Resolution: ±0.01 in w.c.
Internal Thermistor Resolution: 0.7°F (0.4°C), R25 value equal to 10,000Ω [10kΩ @ 25°C (77°F)].
Resolution: 12 bits (1 in 4096).
Nonlinearity: ±0.05% FS (BFSL).
Hysteresis and Repeatability: ±0.05% FS.
Drift: ±0.5% FS/yr.
Sampling Methods: Continuous (first-in, first-out: not available from 40 ms to 8 s), stop when full (fill-then-stop), or delayed start.

Sampling Rates: Selectable from 0.04 s to 8 hrs.

Ambient Operating Temperature/RH: -40 to 158°F (-40 to 70°C), 0 to 95% RH, non-condensing.

Connection: Two 1/8" ID permanent protective tubing.

Computer Requirements: IBM compatible 386 or above and Windows® 3.1 or later with 2 MB RAM and 2 MB hard drive disk space, one serial port.

Service: Dry air and noncorrosive gases.

Max. Pressure Rating: 4X rated pressure.

Power Requirements: 3.6 V TL5134 lithium metal battery, internal, factory replaceable.

Housing Material: Polyphenylene ether and polystyrene PPE & PS.

Weight: 4 oz (110 g).
Agency Approvals: CE.